



EUCLID CHEMICAL

The Euclid Chemical Company
19215 Redwood Road
Cleveland, OH 44110-2735
Phone: 800-321-7628
Fax: 216-486-8101
www.euclidchemical.com

CHEMICAL RESISTANCE CHART E3 EPOXY GROUTS

	E3-Deep Pour	E3-Flowable	E3-HCR
Solvent			
Acetone	1	1	1
Butyl Acetate	1	1	1
Isopropyl Alcohol, 70%	1	1	1
MEK	1	1	1
Mineral Spirits	2	1	1
Acids			
Acetic, 10%	NR	3	3
Acetic, 25%	NR	NR	NR
Acetic, 50%	NR	NR	NR
Hydrochloric, 10%	1	1	1
Hydrochloric, 37%	1	1	1
Sulfuric, 10%	1	1	1
Sulfuric, 50%	3	1	1
Sulfuric, 98%	NR	NR	1
Bases/Alkalies			
Sodium Chloride, 50%	1	1	1
Sodium Hydroxide, 1-50%	1	1	1
Miscellaneous			
Diesel	1	1	1
Gas	3	1	1

Rating Key

1 = Long term Exposure (30 days)

2 = Extended Exposure (7 days)

3 = Splash / Spill (3 days)

NR = Not Recommended