



INCRETE CLEAR SEAL NATURAL

DECORATIVE CONCRETE WATER-BASED COLOR ENHANCING SEALER EUCLID CHEMICAL

PACKAGING

5 gal (18.9 L) pails
Cases of 1 gal (3.8 L) jugs

YIELD

First Coat: 150 to 350 ft²/gal
(3.7 to 8.6 m²/L)

Second Coat: 200 to 400 ft²/gal
(4.9 to 9.8 m²/L)

APPEARANCE

White, opaque liquid

CLEAN UP

Clean tools and spray equipment immediately with water. Clean spills, drips, or overspray with water while still wet.

SHELF LIFE

1 year in original, unopened package

SPECIFICATIONS AND COMPLIANCES

ASTM C 1315, Type 1, Class A
ASTM C 309, Type 1, Class A & B

BRIEF OVERVIEW

INCRETE CLEAR SEAL NATURAL is a ready-to-use, water-based, silicone water repellent sealer. INCRETE CLEAR SEAL NATURAL works by impregnating the surface forming a hydrophobic barrier with excellent water beading characteristics that protects concrete, pavers, and stone. INCRETE CLEAR SEAL NATURAL is not a film-forming topical sealer. INCRETE CLEAR SEAL NATURAL is breathable and preserves the natural look of the surface, without adding gloss but nicely enhances the color of the substrate.

PRODUCT CHARACTERISTICS

ADVANTAGES

- Color enhancing
- Excellent water beading
- Not a film-forming sealer
- Natural look - no gloss
- Good tire marking resistance
- Excellent blush resistance
- Non-yellowing
- Low VOC - low odor
- Can contribute to LEED points (EQ Credit 4.2)

COMMON USES

- Stamped concrete
- Decorative concrete
- Integrally-colored concrete
- Natural & cultured stone
- Pavers & pre-cast units
- Driveways & sidewalks
- Patios
- Walls

COMMON APPLICATION METHODS

- Sprayer
- Brush
- Roller

TECHNICAL INFORMATION

Material Properties at 75°F (24°C), 50% Relative Humidity

Drying Time	Less than 1 hour
Foot Traffic	4 to 6 hours
Wheel Traffic	6 to 10 hours

VOC Content	< 50 g/L
Viscosity	5 cp

INCRETE CLEAR SEAL NATURAL is a white, opaque liquid. After application and drying, the product is clear, and will not add gloss like a topical, film-forming coating. INCRETE CLEAR SEAL NATURAL may slightly darken some substrates. A small test area is strongly recommended to confirm appearance prior to beginning full application.

DIRECTIONS FOR USE

SURFACE PREPARATION

The surface must be structurally sound, clean and free of curing compounds, sealers, grease, oil, dust, soil, and other contaminants. New concrete must be at least 7 days old. Prior to application, surface defects, voids, cracks, and joints should be properly treated and/or repaired. Allow surface to dry prior to application.

MIXING

Stir/agitate INCRETE CLEAR SEAL NATURAL prior to application.

APPLICATION

Apply INCRETE CLEAR SEAL NATURAL in an even, continuous film by sprayer, short nap roller, brush, or a combination of the above. Apply the second coat of INCRETE CLEAR SEAL NATURAL using a "wet on wet" method, before the first coat has dried. Typically, the second coat will need to be applied within 10 to 20 minutes of applying the first coat, although drying times will vary with weather conditions. Re-distribute or soak up puddles of INCRETE CLEAR SEAL NATURAL that have not penetrated into the substrate after 10 to 20 minutes. Allowing puddles to dry on surface may lead to higher gloss and tackiness in those areas.

PRECAUTIONS/LIMITATIONS

- Store INCRETE CLEAR SEAL NATURAL indoors, protected from moisture, at temperatures between 50°F and 90°F (10°C and 32°C)
- Surface and ambient temperature during coating applications should be between 45°F and 105°F (7°C and 41°C)
- Do not apply INCRETE CLEAR SEAL NATURAL to frost-filled or frozen substrates
- Do not apply INCRETE CLEAR SEAL NATURAL if rain or heavy fog is expected within 4 hours of application
- Material temperatures should be at least 50°F (10°C) and rising
- Do not thin INCRETE CLEAR SEAL NATURAL
- Application of a test area is strongly recommended to confirm final appearance and texture of the sealer with the end user
- INCRETE CLEAR SEAL NATURAL will enhance color and darken substrates. However, color enhancement may be lower when applying INCRETE CLEAR SEAL NATURAL to polymer/latex-modified cementitious mortars and overlays.
- INCRETE CLEAR SEAL NATURAL does not cure concrete, and is not intended for use as a curing compound
- Do not apply INCRETE CLEAR SEAL NATURAL over existing curing compounds or curing & sealing compounds
- Do not allow puddles of INCRETE CLEAR SEAL NATURAL to dry on surface during application. If puddles are allowed to dry, the affected areas may have a higher gloss and tackiness.
- Applying thicker than recommended, applying in cool/cold weather, or prolonged exposure to moisture (high humidity, rain, etc.) may result in the sealer remaining soft/wet/tacky for longer than the times found on this data sheet.
- In all cases, consult the product Safety Data Sheet before use

Rev. 07.21

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.