

Revision Date: 11/11/2022

SAFETY DATA SHEET

1. Identification

Material name: EUCO CABLE GROUT PTX

Material: 088L 50

Recommended use and restriction on use

Recommended use: Cement, Portland, chemicals

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110

US

Contact person: EH&S Department **Telephone:** 216-531-9222

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Inhalation - dust and Category 4

mist)

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 1
Skin sensitizer Category 1
Carcinogenicity Category 1A
Specific Target Organ Toxicity - Category 3¹

Single Exposure

Specific Target Organ Toxicity - Category 1²

Repeated Exposure

Target Organs

1. Respiratory tract irritation.

2. Lung

Unknown toxicity - Health

Acute toxicity, oral 81.29 %
Acute toxicity, dermal 84.18 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust 98.13 %

or mist

Label Elements



EUCLID CHEMICAL

Version: 4.1

Revision Date: 11/11/2022

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage. May cause an allergic skin reaction.

May cause cancer.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention: Use only outdoors or in a well-ventilated area. Wash thoroughly after

handling. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Do

not eat, drink or smoke when using this product.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Immediately call a POISON CENTER/doctor. Specific treatment (see on this label). Wash contaminated clothing before

reuse.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly

closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures



Revision Date: 11/11/2022

Chemical Identity	CAS number	Content in percent (%)*
Portland cement	65997-15-1	50 - <100%
Silica, fused	60676-86-0	20 - <50%
Fumed silica	69012-64-2	10 - <20%
Calcium oxide	1305-78-8	1 - <3%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	1 - <5%
Aluminum oxide	1344-28-1	1 - <5%
Iron oxide	1309-37-1	0.1 - <1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Move to fresh air.

Skin Contact: Get medical attention. Destroy or thoroughly clean contaminated

> shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic

skin reaction develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Call a physician or poison control

center immediately.

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Personal Protection for Firstaid Responders:

Self-contained breathing apparatus and full protective clothing must

be worn in case of fire.

Most important symptoms/effects, acute and delayed

Symptoms: Prolonged or repeated contact with skin may cause redness, itching,

irritation and eczema/chapping. Extreme irritation of eyes and mucous membranes, including burning and tearing. Respiratory tract irritation.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.



Revision Date: 11/11/2022

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and

emergency procedures:

See Section 8 of the SDS for Personal Protective Equipment. Do not touch

damaged containers or spilled material unless wearing appropriate

protective clothing. Keep unauthorized personnel away.

Accidental release measures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Methods and material for containment and cleaning

up:

Collect spillage in containers, seal securely and deliver for disposal

according to local regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure

limits and minimize the risk of inhalation of dust.

Safe handling advice: Ventilate well, avoid breathing vapors. Use approved respirator if air

contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not get in eyes. Wash hands thoroughly after handling. Avoid contact with skin. Avoid

contact with eyes, skin, and clothing.

Contact avoidance measures: No data available.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Do not get in eyes. Wash

contaminated clothing before reuse. Avoid contact with skin. Contaminated

work clothing should not be allowed out of the workplace.

Storage

Safe storage conditions: Store locked up.



Revision Date: 11/11/2022

Safe packaging materials: No data available.

8. Exposure controls/personal protection

Control Parameters

occupational Exposure L	imits		
Chemical Identity	Туре	Exposure Limit Values	Source
Portland cement - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Portland cement - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Portland cement - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Portland cement	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Silica, fused	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Fumed silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Fumed silica - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Fumed silica - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Fumed silica - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Fumed silica - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Fumed silica - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Fumed silica - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (2008)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_AC T	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)



EUCLID CHEMICAL

Revision Date: 11/11/2022

	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended (02 2020)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Aluminum oxide - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Iron oxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Iron oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)





Revision Date: 11/11/2022

Chemical name	mical name Type Exposure Limit Values		Source	
Portland cement - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
Portland cement - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
Portland cement - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017)	
Portland cement - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)	
Silica, fused - Respirable fraction.	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)	
Silica, fused - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
Fumed silica - Respirable fume.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Fumed silica - Respirable fraction.	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)	
Fumed silica - Respirable dust and/or fume.	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
Fumed silica - Total fume.	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2021)	
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)	
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)	
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)	
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)	
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)	
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)	
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and	



Revision Date: 11/11/2022

			safety), as amended (09 2017)
Aluminum oxide - Respirable.	TWA	1.0 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Aluminum oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Aluminum oxide - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Aluminum oxide - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)

Appropriate Engineering

Controls

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure

limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear a full-face respirator, if needed. Wear safety glasses with side shields

(or goggles) and a face shield.

Skin Protection

Hand Protection: Additional Information: Use suitable protective gloves if risk of skin contact.

Skin and Body Protection: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Do not get in eyes. Wash

contaminated clothing before reuse. Avoid contact with skin. Contaminated

work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Powder
Color: Gray
Odor: Odorless

Odor threshold:

pH:

No data available.

No data available.

Melting point/freezing point:

No data available.



Revision Date: 11/11/2022

Initial boiling point and boiling range:No data available.Flash Point:No data available.Evaporation rate:No data available.

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

No data available.

No data available.

Vapor pressure:

No data available.

No data available.

No data available.

Relative density: 3.0

Solubility(ies)

Solubility in water: Miscible with water.
Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Eye contact: Causes serious eye damage.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics



Revision Date: 11/11/2022

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 5,118.49 mg/kg

Dermal

Product: ATEmix: 13,700.35 mg/kg

Inhalation

Product: ATEmix: 1.9 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Crystalline Silica

(Quartz)/ Silica

Sand

Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica Known To Be Human Carcinogen.

(Quartz)/ Silica

Sand



Revision Date: 11/11/2022

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

Crystalline Silica

(Quartz)/ Silica Cancer

Sand

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Single Exposure: Respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure: Lung

Aspiration Hazard

Product: No data available.

Other effects: Constituents of this product may include crystalline silica which, if in

inhalable form, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic

or cause other serious lung problems.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:



Revision Date: 11/11/2022

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated



Revision Date: 11/11/2022

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

Chemical IdentityOSHA hazard(s)Crystalline Silicakidney effects(Quartz)/ Silica Sandlung effects

immune system effects

Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Acute toxicity

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Serious Eye Damage/Eye imialion

Skin sensitizer Carcinogenicity

Specific Target Organ Toxicity - Single Exposure

Specific Target Organ Toxicity - Repeated Exposure

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

Chemical Identity % by weight

Aluminum oxide 1.0%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.



Revision Date: 11/11/2022

US State Regulations

US. California Proposition 65

For more information go to www.P65Warnings.ca.gov.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and

exempt solvent)

VOC Method 310 : 0.00 %

< 5 g/l



Revision Date: 11/11/2022

Inventory Status:

Australia AICS: One or more components in this

product are not listed on or exempt

from the Inventory.

EINECS, ELINCS or NLP: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

One or more components in this product are not listed on or exempt

from the Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are

listed on or exempt from the

Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Philippines PICCS: One or more components in this

product are not listed on or exempt

from the Inventory.

US TSCA Inventory: All components in this product are

listed on or exempt from the

Inventory.

New Zealand Inventory of Chemicals: All components in this product are

listed on or exempt from the

Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Canada DSL Inventory List: All components in this product are

listed on or exempt from the

Inventory.



Revision Date: 11/11/2022

16.Other information, including date of preparation or last revision

Revision Date: 11/11/2022

Version #: 4.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.