



# EUCON™ FOR-CAST™ SC

PLASTICIZING ADMIXTURE FOR MANUFACTURED CONCRETE PRODUCTS

EUCLID CHEMICAL

## PRODUCT INFORMATION

### PACKAGING

Available in bulk, 275 gal (1041 L) totes, 55 gal (208 L) drums, and 5 gal (18.9 L) pails

### SHELF LIFE

1 year in original, unopened container

### TECHNICAL INFORMATION

Appearance: Amber Liquid

Specific Gravity ~ 1.03

Freezing Point ~ 20°F (-6.7°C)

## DESCRIPTION

EUCON FOR-CAST SC swiipe producing, concentrated plasticizer was formulated to improve the manufacturing efficiency, consistency, and visual appeal of machine made concrete products. EUCON FOR-CAST SC adds mix flowability, cement efficiency, and cost effectively modifies the texture of formed concrete surfaces. EUCON FOR-CAST SC also improves edge and corner definition, and reduces the potential for chipping.

## PRODUCT CHARACTERISTICS

### FEATURES & BENEFITS

- Improves production cycle times
- Sharpens edge and corner definition
- Economically modifies surface texture
- Enhances freeze thaw durability
- Reduces wear of molds and profilers

### PRIMARY APPLICATIONS

- Concrete block and brick
- Concrete pavers, patio products
- Segmental retaining wall units
- Dry cast concrete pipe
- Extruded hollow core slabs
- Concrete roofing tile

## PRECAUTIONS/LIMITATIONS

- Mix trials are recommended to determine dosage. Contact your Euclid Chemical sales representative for any assistance.
- If frozen, EUCON FOR-CAST SC can be reconstituted by mechanical means - never agitate with air.
- In all cases, consult the Safety Data Sheet before use.

## DIRECTIONS FOR USE

EUCON FOR-CAST SC may be introduced with initial mix water or after the cement has been added with water. Never add EUCON FOR-CAST SC directly on dry cement. Mix thoroughly as determined by mixer type. EUCON FOR-CAST SC is intended for use at a rate of 0.5 - 3 oz/100 lbs. (33 - 196 mL/100 kg) of cementitious materials and is compatible with all Euclid Chemical manufactured concrete admixtures.

**WARRANTY:** The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.